



# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet PRO21-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/11/2015

Revision date: 07/09/2019

Supersedes: 04/30/2019

Version: 4.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : EUROPRIME 4:1 HS PRIMER  
Product code : PRO21

#### 1.2. Recommended use and restrictions on use

Recommended use : Primer

#### 1.3. Supplier

PRO LINE PERFORMANCE PRODUCTS  
P.O. Box PO BOX 1136  
WA 98507 - USA  
[admin@prolineperformanceproducts.com](mailto:admin@prolineperformanceproducts.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec : 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 3	Flammable liquid and vapor
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Flammable liquid and vapor  
Causes skin irritation  
Causes serious eye irritation  
Suspected of causing cancer  
May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS US) :

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe fume, spray, vapors.  
Wash hands thoroughly after handling.  
Wear face protection, protective clothing, protective gloves.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If exposed or concerned: Get medical advice/attention.  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use foam, extinguishing powder, dry sand to extinguish.  
Store in a well-ventilated place. Keep cool.

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

4.34% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
talc	(CAS-No.) 14807-96-6	5 - 23	Carc. 2, H351
xylene	(CAS-No.) 1330-20-7	5 - 23	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
reaction mass of ethylbenzene, m-xylene and p-xylene		< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
titanium(IV) oxide	(CAS-No.) 13463-67-7	< 5	Carc. 2, H351
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethylbenzene	(CAS-No.) 100-41-4	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Water.

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.  
Reactivity : Flammable liquid and vapor.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Safety glasses. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain released product.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.  
Storage temperature : < 25 °C  
Storage area : Store in well ventilated area.  
Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

titanium(IV) oxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethylbenzene (100-41-4)</b>		
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>		
Not applicable		
<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>		
Not applicable		
<b>xylene (1330-20-7)</b>		
ACGIH	Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>talc (14807-96-6)</b>		
ACGIH	Local name	Talc
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica)
ACGIH	ACGIH TWA (ppm)	0.1 fibers/cm <sup>3</sup> (Containing asbestos fibers. F - Respirable fibers)
ACGIH	Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Gas mask. Gloves. Protective clothing. Safety glasses.

#### Materials for protective clothing:

Impermeable clothing

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous. Liquid. : Gray : aromatic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 28 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.69 (1.67 - 1.71) g/cm <sup>3</sup>
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 4142.012 mm <sup>2</sup> /s
Viscosity, dynamic	: 7000 (6500 - 7500) cP
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

As Packaged Regulatory VOC	: 400 g/l (3.33 lb/gal)
As Packaged Actual VOC	: 400 g/l (3.33 lb/gal)
As Applied Regulatory VOC	: 513 g/l (4.3 lb/gal)
As Applied Actual VOC	: 513 g/l (4.3 lb/gal)
Water Content	0 wt%
Exempt Compounds by volume	: 0 vol %

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Exempt Compounds by weight	: 0 wt%
Volatiles	: 23.8 wt%
% HAPS	: 11.1 wt%
Percent Solids	: 76.23 wt%
Percent Solids	: 50.14 vol %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Unknown acute toxicity (GHS US)	4.34% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
---------------------------------	---

#### titanium(IV) oxide (13463-67-7)

LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

#### ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	17.8 mg/l/4h

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

LD50 oral rat	3592 mg/kg (OECD Test Guideline 401, rat)
LD50 dermal rabbit	> 3160 mg/kg (OECD Test Guideline 402)
ATE US (oral)	3592 mg/kg body weight

#### reaction mass of ethylbenzene, m-xylene and p-xylene

LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral), rat, male))
LD50 dermal rabbit	12126 mg/kg (Weight of evidence, New Zealand White)
LC50 inhalation rat (ppm)	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	6350 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg body weight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LC50 inhalation rat (ppm)	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	6700 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>talc (14807-96-6)</b>	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

<b>titanium(IV) oxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>xylene (1330-20-7)</b>	
IARC group	3 - Not classifiable

<b>talc (14807-96-6)</b>	
IARC group	3 - Not classifiable, 2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
STOT-single exposure	May cause respiratory irritation.

<b>xylene (1330-20-7)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).
------------------------	--

<b>ethylbenzene (100-41-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day ( OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>xylene (1330-20-7)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: 4142.012 mm <sup>2</sup> /s

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after eye contact : Eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>titanium(IV) oxide (13463-67-7)</b>	
LC50 fish 1	100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

<b>ethylbenzene (100-41-4)</b>	
LC50 fish 1	4.2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Salmo gairdneri, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	2.1 (1.8 - 2.4) mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LC50 fish 1	3300 - 4093 µg/l
EC50 Daphnia 1	2930 - 4000 µg/l

<b>xylene (1330-20-7)</b>	
LC50 fish 1	2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal)
ErC50 (algae)	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

<b>talc (14807-96-6)</b>	
LC50 fish 1	89581 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)

#### 12.2. Persistence and degradability

<b>titanium(IV) oxide (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance

<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

<b>xylene (1330-20-7)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.

<b>talc (14807-96-6)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

#### 12.3. Bioaccumulative potential

<b>titanium(IV) oxide (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.



# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethylbenzene (100-41-4)</b>	
BCF fish 1	1 - 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value)
Log Pow	3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>solvent naphtha (petroleum), light aromatic (64742-95-6)</b>	
Log Pow	2.1 - 6
Bioaccumulative potential	Not established.
<b>xylene (1330-20-7)</b>	
BCF fish 1	7.2 - 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Log Pow	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>talc (14807-96-6)</b>	
BCF other aquatic organisms 1	3.162 l/kg (BCFBAF v3.01, Fresh water, QSAR)
Log Pow	-9.4 (QSAR, KOWWIN, 25 °C)
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

<b>titanium(IV) oxide (13463-67-7)</b>	
Ecology - soil	Low potential for mobility in soil.
<b>ethylbenzene (100-41-4)</b>	
Surface tension	0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension)
Log Koc	2.71 (log Koc, PCKOCWIN v1.66, QSAR)
Ecology - soil	Low potential for adsorption in soil. Toxic to soil organisms.
<b>xylene (1330-20-7)</b>	
Surface tension	28.01 - 29.76 mN/m (25 °C)
Log Koc	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.
<b>talc (14807-96-6)</b>	
Log Koc	1.5 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : III - Minor Danger  
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
Other information : No supplementary information available.

### Transportation of Dangerous Goods

Transport document description : UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III  
UN-No. (TDG) : UN1263  
Proper Shipping Name (Transportation of Dangerous Goods) : PAINT  
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids  
Packing group : III - Minor Danger  
TDG Special Provisions : 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20 per cent nitrocellulose if the nitrocellulose contains not more than 12.6 per cent nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material. SOR/2014-306  
Explosive Limit and Limited Quantity Index : 5 L  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60 L

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

Transport document description (IMDG)	: UN 1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

### Air transport

Transport document description (IATA)	: UN 1263 Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III, ENVIRONMENTALLY HAZARDOUS
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene	CAS-No. 100-41-4	< 5%
xylene, mixture of isomers	CAS-No. 1330-20-7	5 - 23%

#### titanium(IV) oxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 1000 lb

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 100 lb

#### talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

#### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

# EUOPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the Canadian DSL (Domestic Substances List)

### xylene (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

### talc (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

#### ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
carbon black(1333-86-4)	X					
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	

Component	State or local regulations
ethylbenzene(100-41-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
xylene(1330-20-7)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
talc(14807-96-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
titanium(IV) oxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/09/2019


# EUROPRIME 4:1 HS PRIMER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

- |                    |  |
|--------------------|--|
| NFPA health hazard | : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.                     |
| NFPA fire hazard   | : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. |
| NFPA reactivity    | : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.       |



SDS US GHS (GHS HazCom2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*