

Version 1.0 Revision Date: 04/07/2023

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : PRO LINE LACQUER THINNER REV

Recommended use of the chemical and restrictions on use

Recommended use : Industrial chemical

Manufacturer or supplier's details

Company : ASC Distributing
Address P.O Box 1136

Olympia, WA 98507

United States of America (USA)

**Emergency telephone number:** 

ASC Distributing:-1-800-424-9300

Additional Information: : Phone: 206-363-0747

Regulatory Information Number: 425-771-0926

Email: jh@wescogroupinc.com

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

: Category 1 (Eyes, Central nervous system)

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

Specific target organ toxicity

- repeated exposure

(Inhalation)

: Category 2 (Auditory system, Eyes)

Aspiration hazard : Category 1

GHS label elements

SDS Number: 100000073220 1 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Hazard pictograms









Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or

if inhaled.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child. H370 Causes damage to organs (Eyes, Central nervous sys-

tem).

H373 May cause damage to organs (Auditory system, Eyes)

through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention**:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/

physician.

P331 Do NOT induce vomiting.



Version 1.0 Revision Date: 04/07/2023

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

| CAS-No.       | Chemical name                                  | Weight percent |
|---------------|--|----------------|
| 67-56-1       | Methanol                                       | 50 - 70        |
| 108-88-3      | Toluene  | 20 - 30        |
| 67-64-1       | Acetone  | 10 - 20        |
| 64742-49-0 /  | Naphtha (pet), hydrotreated It AND/OR Heptane, | 5 - 10         |
| 426260-76-6 / | branched, cyclic and linear AND/OR Solvent     |                |
| 64742-89-8    | naphtha (pet), It aliph.                       |                |
| 142-82-5      | **Heptane                                      | 1 - 5          |

Actual concentration is withheld as a trade secret

Any Concentration shown as a range is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

SDS Number: 100000073220 3 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing me-

dia

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: Carbon oxides formaldehyde

toxic fumes

Unburned hydrocarbons

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absor-

bent material, (e.g. sand, earth, diatomaceous earth,

SDS Number: 100000073220 4 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

vermiculite) and place in container for disposal according to local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

Advice on safe handling

fire and explosion

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

ŭ

: Avoid formation of aerosol. Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the appli-

cation area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Components with workplace control parameters

| CAS-No. | Components | Value type   | Control parame-    | Basis     |
|---------|------------|--------------|--------------------|-----------|
|         |            | (Form of ex- | ters / Permissible |           |
|         |            | posure)      | concentration      |           |
| 67-56-1 | Methanol   | TWA          | 200 ppm            | ACGIH     |
|         |            | STEL         | 250 ppm            | ACGIH     |
|         |            | TWA          | 200 ppm            | NIOSH REL |
|         |            |              | 260 mg/m3          |           |
|         |            | ST           | 250 ppm            | NIOSH REL |
|         |            |              | 325 mg/m3          |           |
|         |            | TWA          | 200 ppm            | OSHA Z-1  |
|         |            |              | 260 mg/m3          |           |
|         |            | STEL         | 250 ppm            | OSHA P0   |
|         |            |              | 325 mg/m3          |           |
|         |            | TWA          | 200 ppm            | OSHA P0   |
|         |            |              | 260 mg/m3          |           |
|         |            | С            | 1,000 ppm          | CAL PEL   |



SDS Number: 100000073220

# Safety Data Sheet PRO LINE LACQUER THINNER REV

Version 1.0 Revision Date: 04/07/2023

|   |   | PEL  | 200 ppm<br>260 mg/m3     | CAL PEL   |
|---|---|------|--------------------------|-----------|
|   |   | STEL | 250 ppm<br>325 mg/m3     | CAL PEL   |
| 108-88-3                                    | Toluene   | TWA  | 20 ppm                   | ACGIH     |
|   |   | TWA  | 100 ppm<br>375 mg/m3     | NIOSH REL |
|   |   | ST   | 150 ppm<br>560 mg/m3     | NIOSH REL |
|   |   | TWA  | 200 ppm                  | OSHA Z-2  |
|   |   | CEIL | 300 ppm                  | OSHA Z-2  |
|   |   | Peak | 500 ppm                  | OSHA Z-2  |
|   |   | TWA  | 100 ppm<br>375 mg/m3     | OSHA P0   |
|   |   | STEL | 150 ppm<br>560 mg/m3     | OSHA P0   |
|   |   | PEL  | 10 ppm<br>37 mg/m3       | CAL PEL   |
|   |   | С    | 500 ppm                  | CAL PEL   |
|   |   | STEL | 150 ppm<br>560 mg/m3     | CAL PEL   |
| 67-64-1                                     | Acetone   | TWA  | 250 ppm                  | ACGIH     |
| -   |   | STEL | 500 ppm                  | ACGIH     |
|   |   | TWA  | 250 ppm<br>590 mg/m3     | NIOSH REL |
|   |   | TWA  | 1,000 ppm<br>2,400 mg/m3 | OSHA Z-1  |
|   |   | TWA  | 750 ppm<br>1,800 mg/m3   | OSHA P0   |
|   |   | STEL | 1,000 ppm<br>2,400 mg/m3 | OSHA P0   |
|   |   | STEL | 750 ppm<br>1,780 mg/m3   | CAL PEL   |
|   |   | С    | 3,000 ppm                | CAL PEL   |
|   |   | PEL  | 500 ppm<br>1,200 mg/m3   | CAL PEL   |
| 64742-49-0 /<br>426260-76-6 /<br>64742-89-8 | Naphtha (pet), hydrotreated It<br>AND/OR Heptane, branched,<br>cyclic and linear AND/OR Sol-<br>vent naphtha (pet), It aliph. | TWA  | 400 ppm                  | ACGIH     |
|   |   | STEL | 500 ppm                  | ACGIH     |
| 142-82-5                                    | **Heptane   | TWA  | 85 ppm<br>350 mg/m3      | NIOSH REL |
|   |   | С    | 440 ppm<br>1,800 mg/m3   | NIOSH REL |
|   |   | TWA  | 500 ppm<br>2,000 mg/m3   | OSHA Z-1  |
|   |   | TWA  | 400 ppm<br>1,600 mg/m3   | OSHA P0   |
|   |   | STEL | 500 ppm<br>2,000 mg/m3   | OSHA P0   |
|   |   | TWA  | 400 ppm                  | ACGIH     |



Version 1.0 Revision Date: 04/07/2023

STEL 500 ppm ACGIH

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying

respirators may not provide adequate protection.

In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the

product.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : Clear, colorless
Odour : No data available
Odour Threshold : No data available
pH : No data available

Freezing Point : No data available Boiling Point : No data available Flash point : -9 °C (16 °F)

Evaporation rate : No data available Flammability (solid, gas) : No data available Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

SDS Number: 100000073220 7 / 17 PRO LINE LACQUER THINNER REV



# **Safety Data Sheet**

# PRO LINE LACQUER THINNER REV

Version 1.0 Revision Date: 04/07/2023

Relative vapour density : No data available

Relative density : 0.796

Density : 0.796 g/cm3

Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-oc- : No data available

tanol/water

Auto-ignition temperature : No data available Thermal decomposition : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Alkali metals Amines Bases halogens

Oxidizing agents peroxides

Reducing agents

# **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 172.41 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 5.17 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : Acute toxicity estimate: 517.24 mg/kg

**Components:** 

67-56-1:

Acute oral toxicity : Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation.

SDS Number: 100000073220 8 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU

Harmonized Classification (Annex VII).

Acute dermal toxicity : Assessment: The component/mixture is toxic after single con-

tact with skin.

64742-49-0 / 426260-76-6 / 64742-89-8:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 73.5 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

#### **Product:**

Remarks: May cause skin irritation in susceptible persons.

# **Components:**

108-88-3:

Species: Rabbit Exposure time: 4 h Result: Irritating to skin.

#### 64742-49-0 / 426260-76-6 / 64742-89-8:

Species: Rabbit Exposure time: 24 h Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

### Serious eye damage/eye irritation

# **Product:**

Remarks: May cause irreversible eye damage.

# **Components:**

108-88-3:

Species: Rabbit

Result: Irritating to eyes.

67-64-1:

Species: Rabbit

Result: Irritating to eyes. Exposure time: 24 h



Version 1.0 Revision Date: 04/07/2023

#### 64742-49-0 / 426260-76-6 / 64742-89-8:

Result: No eye irritation

#### Respiratory or skin sensitisation

#### **Components:**

#### 64742-49-0 / 426260-76-6 / 64742-89-8:

Test Type: Maximization test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Based on a similar product formulation.

# Germ cell mutagenicity

# **Components:**

108-88-3:

Germ cell mutagenicity - As-

sessment

: Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

#### 64742-49-0 / 426260-76-6 / 64742-89-8:

sessment

Germ cell mutagenicity - As- : Mutagenicity classification not possible from current data

### Carcinogenicity

# **Components:**

108-88-3:

Carcinogenicity - Assess-

: No evidence of carcinogenicity in animal studies.

ment

# 64742-49-0 / 426260-76-6 / 64742-89-8:

Carcinogenicity - Assess-

: Not classifiable as a human carcinogen.

ment

**IARC** 

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed hu-

man carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# Reproductive toxicity

# Components:

108-88-3:

Effects on foetal develop-

ment

: Species: Rat

Application Route: inhalation (vapour) Dose: 0, 250, 750, 1500, 3000 ppm Duration of Single Treatment: 10 d

SDS Number: 100000073220 10 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Frequency of Treatment: 6 hr/day

General Toxicity Maternal: NOAEC: 750 ppm Developmental Toxicity: NOAEC: 750 ppm

Symptoms: Maternal toxicity, Reduced body weight, Skeletal

malformations

Teratogenicity - Assessment : Some evidence of adverse effects on development, based on

animal experiments.

Reproductive toxicity - As-

sessment

No toxicity to reproduction

64742-49-0 / 426260-76-6 / 64742-89-8:

Reproductive toxicity - As-

sessment

Fertility classification not possible from current data.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

#### STOT - single exposure

# **Components:**

#### 67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

## 108-88-3:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as spe-

cific target organ toxicant, single exposure, category 3 with narcotic effects.

# 67-64-1:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as spe-

cific target organ toxicant, single exposure, category 3 with narcotic effects.

### 64742-49-0 / 426260-76-6 / 64742-89-8:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as spe-

cific target organ toxicant, single exposure, category 3 with narcotic effects.

#### STOT - repeated exposure

# **Components:**

### 108-88-3:

Exposure routes: Inhalation

SDS Number: 100000073220 11 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Target Organs: Auditory system, Eyes

Assessment: May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

# **Aspiration toxicity**

#### Components:

108-88-3:

May be fatal if swallowed and enters airways.

64742-49-0 / 426260-76-6 / 64742-89-8:

May be fatal if swallowed and enters airways.

#### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

# **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### Components:

108-88-3:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Ceriodaphnia dubia): 3.78 mg/l

Exposure time: 48 h Test Type: Renewal

Toxicity to daphnia and other : NOEC: 0.74 mg/l

aquatic invertebrates

Exposure time: 7 d

(Chronic toxicity)

Acute aquatic toxicity- As-

sessment

: Toxic to aquatic life.

Chronic aquatic toxicity- As-

sessment

: Harmful to aquatic life with long lasting effects.

64742-49-0 / 426260-76-6 / 64742-89-8:

Toxicity to fish : LC50 (Carassius auratus (goldfish)): 4 mg/l

Exposure time: 24 h

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 1.5 mg/l

Exposure time: 48 h Test Type: static test

SDS Number: 100000073220 12 / 17 PRO LINE LACQUER THINNER REV



Version 1.0 Revision Date: 04/07/2023

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7

Exposure time: 96 h Test Type: static test

Acute aquatic toxicity- As-

sessment

Chronic aquatic toxicity- As-

sessment

: Very toxic to aquatic life.

: Very toxic to aquatic life with long lasting effects.

### Persistence and degradability

### Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Biodegradability : aerobic

> Inoculum: activated sludge Biodegradation: 74.30 % Exposure time: 56 d

Remarks: Inherently biodegradable.

# **Bioaccumulative potential**

#### Components:

108-88-3:

Partition coefficient: n-oc-: log Pow: 2.73 (20 °C)

tanol/water pH: 7

64742-49-0 / 426260-76-6 / 64742-89-8:

Partition coefficient: n-oc-

: log Pow: 2.13 - 4.85 (25 °C)

Mobility in soil

tanol/water

No data available

# Other adverse effects

# **Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.



# **Safety Data Sheet**

# PRO LINE LACQUER THINNER REV

Version 1.0 Revision Date: 04/07/2023

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

**DOT (Department of Transportation):** 

UN1993, Flammable liquids, n.o.s., (TOLUENE, METHANOL), 3, II

IATA (International Air Transport Association):

UN1993, FLAMMABLE LIQUID, N.O.S., (TOLUENE, METHANOL), 3, II

**IMDG** (International Maritime Dangerous Goods):

UN1993, FLAMMABLE LIQUID, N.O.S., (TOLUENE, METHANOL), 3, II, Flash Point:-9 °C(16 °F)

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

| Components | CAS-No.  | Component RQ | Calculated product RQ |
|------------|----------|--------------|-----------------------|
|            |          | (lbs)        | (lbs)                 |
| Toluene    | 108-88-3 | 1000         | 5000                  |
| Methanol   | 67-56-1  | 5000         | 8620                  |

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

67-56-1 Methanol 108-88-3 Toluene

SDS Number: 100000073220 14 / 17 PRO LINE LACQUER THINNER REV



# **Safety Data Sheet**

# PRO LINE LACQUER THINNER REV

Version 1.0 Revision Date: 04/07/2023

#### \*\*Toluene

#### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

67-56-1 Methanol 108-88-3 Toluene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

67-56-1 Methanol 108-88-3 Toluene 67-64-1 Acetone

# **Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3 Toluene 71-43-2 \*\*Benzene 100-41-4 \*\*Ethylbenzene 108-88-3 \*\*Toluene 91-20-3 \*\*Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3 Toluene 71-43-2 \*\*Benzene 100-41-4 \*\*Ethylbenzene 108-88-3 \*\*Toluene 91-20-3 \*\*Naphthalene

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

108-88-3 Toluene

# **Massachusetts Right To Know**

| 67-56-1  | Methanol  |
|----------|-----------|
| 108-88-3 | Toluene   |
| 67-64-1  | Acetone   |
| 142-82-5 | **Heptane |
| 71-43-2  | **Benzene |

# Pennsylvania Right To Know

| 67-56-1  | Methanol |  |
|----------|----------|--|
| 108-88-3 | Toluene  |  |
| 67-64-1  | Acetone  |  |

64742-49-0 / Naphtha (pet), hydrotreated It AND/OR 426260-76-6 / Heptane, branched, cyclic and linear AND/OR Solvent naphtha (pet), It aliph.

142-82-5 \*\*Heptane 71-43-2 \*\*Benzene 100-41-4 \*\*Ethylbenzene

## California Prop 65

**WARNING**: This product can expose you to chemicals including \*\*Benzene, \*\*Ethylbenzene, \*\*Cumene, \*\*Naphthalene, which is/are known to the State of California to cause cancer, and



Version 1.0 Revision Date: 04/07/2023

Methanol, Toluene, \*\*Benzene, \*\*Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# The components of this product are reported in the following inventories:


**TSCA** : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

**PICCS** : On the inventory, or in compliance with the inventory

# **SECTION16. OTHER INFORMATION**

NFPA:



Special hazard

#### HMIS III:

| HEALTH          | 2* |
|-----------------|----|
| FLAMMABILITY    | 3  |
| PHYSICAL HAZARD | 0  |

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 =Extreme, \* = Chronic

**Revision Date** : 04/07/2023

SDS Number: 100000073220

| Key or legend to abbreviations and acronyms used in the safety data sheet |                                  |       |                                     |
|---|----------------------------------|-------|-------------------------------------|
| ACGIH   | American Conference of Govern-   | LD50  | Lethal Dose 50%                     |
|   | ment Industrial Hygienists       |       |                                     |
| AICS  | Australia, Inventory of Chemical | LOAEL | Lowest Observed Adverse Effect      |
|   | Substances                       |       | Level                               |
| DSL   | Canada, Domestic Substances List | NFPA  | National Fire Protection Agency     |
| NDSL  | Canada, Non-Domestic Sub-        | NIOSH | National Institute for Occupational |
|   | stances List                     |       | Safety & Health                     |
| CNS   | Central Nervous System           | NTP   | National Toxicology Program         |
| CAS   | Chemical Abstract Service        | NZloC | New Zealand Inventory of Chemi-     |
|   |                                  |       | cals                                |
| EC50  | Effective Concentration          | NOAEL | No Observable Adverse Effect        |
|   |                                  |       | Level                               |
| EC50  | Effective Concentration 50%      | NOEC  | No Observed Effect Concentration    |
| EGEST   | EOSCA Generic Exposure Sce-      | OSHA  | Occupational Safety & Health Ad-    |
|   | nario Tool                       |       | ministration                        |



SDS Number: 100000073220

# Safety Data Sheet PRO LINE LACQUER THINNER REV

Version 1.0 Revision Date: 04/07/2023

| EOSCA  | European Oilfield Specialty Chemicals Association        | PEL   | Permissible Exposure Limit   |
|--------|--|-------|--|
| EINECS | European Inventory of Existing Chemical Substances       | PICCS | Philippines Inventory of Commercial Chemical Substances                              |
| MAK    | Germany Maximum Concentration Values                     | PRNT  | Presumed Not Toxic   |
| GHS    | Globally Harmonized System                               | RCRA  | Resource Conservation Recovery Act   |
| >=     | Greater Than or Equal To                                 | STEL  | Short-term Exposure Limit  |
| IC50   | Inhibition Concentration 50%                             | SARA  | Superfund Amendments and   |
|        |  |       | Reauthorization Act.   |
| IARC   | International Agency for Research on Cancer              | TLV   | Threshold Limit Value  |
| IECSC  | Inventory of Existing Chemical Substances in China       | TWA   | Time Weighted Average  |
| ENCS   | Japan, Inventory of Existing and New Chemical Substances | TSCA  | Toxic Substance Control Act  |
| KECI   | Korea, Existing Chemical Inventory                       | UVCB  | Unknown or Variable Composition, Complex Reaction Products, and Biological Materials |
| <=     | Less Than or Equal To                                    | WHMIS | Workplace Hazardous Materials<br>Information System                                  |
| LC50   | Lethal Concentration 50%                                 |       |  |